

TECHNICAL DATA SHEET

**LUBRISEAL™ – Tire Lube and Seal****DESCRIPTION:**

With LUBRISEAL, small punctures and bead leaks are a thing of the past. When a puncture or bead leak occurs, microscopic, nontoxic polymer strands suspended in a liquid solution race to the air leak, adhering to the sides of the opening and build a long lasting solid plug, impervious to water, mud, and snow. However, LUBRISEAL stay's in a liquid form and is distributed evenly over the entire inside of the tire.

LUBRISEAL lubricates to help prevent the rusting of tires and wheels. All too often, tire damage occurs when the rim welds itself to the tire due to rust and heat. With LUBRISEAL, this problem is virtually eliminated, which makes removal quick and easy.

USES:

LUBRISEAL is safe and easy to use. It contains no harsh chemicals and safely washes of skin and out of clothing. LUBRISEAL is designed for use in tires found on equipment used in mines, quarries, construction, and all types of off-road applications.

LUBRISEAL provides the following benefits:

- REDUCES COSTLY DOWNTIME
- MAKES TIRE BREAKDOWN QUICK AND EASY
- INCREASES TIRE LIFE
- PREVENTS RUST AND CORROSION DAMAGE TO WHEELS AND RIMS
- INCREASES TIRE LIFE
- EFFECTIVE IN ALL CLIMATES (contains an antifreeze)
- LUBRICATES TO PREVENT TIRES “WELDING” TO RIM

APPLICATION:

LUBRISEAL is designed to be used in low speed off-road tires and nonsteering trailer tires. Do not use in automotive and aviation tires or tires on the steering axel of highway vehicles.

LUBRISEAL RECOMMENDED USAGE AMMOUNTS:

Tractor and Implement Tires		Industrial Tires		Off-Road Tires		Forklift/Loader Mine Equipment	
Size	Pints per Tire	Size	Pints per Tire	Size	Pints per Tire	Size	Pints per Tire
7.50-10	2	3.40/3.00-5	1	7.50-10	2	2.80/2.50-4	1
9.00-10	3	11.00/4.00-5	1	9.00-10	3	4.00-4	1
4.00-15	1	6.90/6.00-6	1	7.50-15	3	4.10/3.50-4	1
5.00-15	2	12.00/11.00-6	3	10.00-15	4	3.50/4	1
5.50-16	2	15.00/6.00-6	2	11.00-16	5	5.30/4.50-6	1
6.50-16	3	16.00/11.50-6	3	7.50-20	4	14/8-6	1
8.00-16	4	4.80/4.00-7	1	9.00-20	4	4.00-8	1
9.00-16	4	5.30/4.50-7	1	10.00-20	6	4.80/4.00-8	1
7.50-25	4	6.50-10	2	11.20-20	7	5.00-8	1
10.00-24	6	9.00-10	3	14.00-20	10	5.70/5.00-8	1
13.00-24	9	15.00-10	6	11.00-24	8	17/16-8	1
14.90/13.00-24	10	4.00-12	1	13.00-24	9	18/7-8	1
16.90/14.00-24	12	7.00-12	2	14.00-24	11	5.00-9	1
12.40/11.00-26	8	23.00/8.50-12	3	15.00-25	13	6.90-9	2
13.60/12.00-26	9	26.00/12.00-12	5	18.00-25	15	_GOLF CARTS	
11.00-28	8	4.00-15	1	20.50-25	16	6.50-5	1
12.30/11.00-28	9	7.50-15	3	24.00-25	24	7.00-6	1
23.10/18.00-30	15	8.25-15	4	18.00-26	16	8.00-6	1
9.00-32	7	27.00/8.50-15	3	26.50-29	26	16/11.50-6	1
28.10-32	7	44.00/41.00-16	40	30.00-33	32	018/8.50-8	1
30.00-33	32	48.00/20.00-16	16	30.00-40	36		
4.00-36	3	4.00-19	2	21.00-49	35		
11.00-36	9	48.00/25.00-20	19				
12.30-11.00-36	9	66.00/43.00-25	50				
13.6/12-36	12	67.00/34.00-25	34				
12.00-36	10						
12.40/11.00-38	10						
30.00-40	47						
36.00-41	47						
30.00-41	36						

LUBRIFORMANCE

2021 Reserve Dr., P.O. Box 1487 Canton, TX 75103 PH: 903-567-7236