

TNT Ultra

SDS Number: 61854

Revision Date: 5/13/2016

Page 1 of 5

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Lubriformance, LLC
2021 Reserve Dr.
Canton, TX 75103

Phone: 1-903-567-7236

Product Name: TNT Ultra
Revision Date: 5/13/2016
SDS Number: 61854
CAS Number: Blend
Product Code: 61854
Synonyms: Diesel Fuel Additive

2 HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

- Physical, Flammable Liquids, 3
- Health, Skin corrosion/irritation, 2
- Health, Serious Eye Damage/Eye Irritation, 2 B
- Health, Acute toxicity, 4 Oral
- Health, Acute toxicity, 4 Dermal
- Health, Acute toxicity, 4 Inhalation
- Health, Specific target organ toxicity - Single exposure, 3
- Health, Carcinogenicity, 2
- Health, Aspiration hazard, 1
- Environmental, Hazards to the aquatic environment - Chronic, 2

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: DANGER

GHS Hazard Pictograms:



GHS Hazard Statements:

- H226 - Flammable liquid and vapor
- H315 - Causes skin irritation
- H320 - Causes eye irritation
- H302 - Harmful if swallowed
- H312 - Harmful in contact with skin
- H332 - Harmful if inhaled
- H335 - May cause respiratory irritation
- H336 - May cause drowsiness or dizziness
- H351 - Suspected of causing cancer
- H304 - May be fatal if swallowed and enters airways
- H411 - Toxic to aquatic life with long lasting effects

GHS Precautionary Statements:

TNT Ultra

SDS Number: 61854

Revision Date: 5/13/2016

Page 2 of 5

- P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking
- P240 - Ground/bond container and receiving equipment.
- P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
- P273 - Avoid release to the environment.
- P302+352 - IF ON SKIN: Wash with soap and water.
- P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- P308+313 - IF exposed or concerned: Get medical advice/attention.

3 COMPOSITION/INFORMATION OF INGREDIENTS

Ingredients:

Chemical Name	Percentage	CAS#
Light aromatic solvent naphtha	30.0 - 60.0	64742-95-6
Ethylene glycol monbutyl ether	20.0 - 40.0	111-76-2
1,2,4-Trimethylbenzene	< 20.0	95-63-6
2-Ethyhexyl nitrate	5.0 - 15.0	27247-96-7
Xylene	< 3.0	1330-20-7
2-Ethylhexanol	1.0 - 5.0	104-76-7
Trimethylbenzene	< 1.0	25551-13-7
Naphthalene	< 1.0	91-20-3
Cumene	< 1.0	98-82-8
Heavy aromatic solvent naphtha	1.0 - 5.0	64742-94-5
1,3,5-Trimethylbenzene	< 0.2	108-67-8
Ethylbenzene	< 0.2	100-41-4
Vinyl acetate monomer	< 0.1	108-05-4

4 FIRST AID MEASURES

- Inhalation:** If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
- Skin Contact:** Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.
- Eye Contact:** Flush with water for several minutes. If effects occur, consult a physician.
- Ingestion:** If swallowed, do NOT induce vomiting. Have the victim rinse mouth with water and then drink 2 - 4 cupfuls of water. Get immediate medical attention.

NOTES TO PHYSICIAN:

Activated charcoal mixture may be administered.

5 FIRE FIGHTING MEASURES

- Flash Point:** 46.1 C (115.0 F)
- Flash Point Method:** PMCC

Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective unless used by experienced fire fighters.

TNT Ultra

SDS Number: 61854

Revision Date: 5/13/2016

Page 3 of 5

6 ACCIDENTAL RELEASE MEASURES

Eliminate sources of ignition - Heat, sparks, flame, and electricity
Contain spilled material.
Collect in suitable and properly labeled containers.
Pick up excess with inert absorbant material
Keep away from drains and ground water.

7 HANDLING AND STORAGE

Handling Precautions: Avoid contact with eyes, skin, or clothing.
Keep away from sources of ignition.
Do not pressurize, cut, weld, braze, solder, drill, or grind container
Handle with care and avoid spillage on the floor (slippage).
Ground and bond containers when transferring material

Storage Requirements: Keep away from sources of ignition.
Store in a tightly closed container

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment: Use of safety glasses and gloves are recommended.

Exposure Guidelines:

- LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)**
OSHA TWA: 500 ppm
- ETHYLENE GLYCOL MONOBUTYL ETHER**
OSHA PEL: 25 ppm, 120 mg/m³
OSHA TWA: 25 ppm
ACGIH TWA: 25 ppm
- 1,2,4-TRIMETHYLBENZENE**
ACGIH TWA: 25 ppm
- XYLENE**
OSHA TWA: 100 ppm, 435 mg/m³
ACGIH TWA: 100 ppm, 434 mg/m³
OSHA STEL: 150 ppm, 655 mg/m³
ACGIH STEL: 150 ppm, 651 mg/m³
- TRIMETHYLBENZENE**
OSHA TWA: 25 ppm, 125 mg/m³
ACGIH TWA: 25 ppm, 123 mg/m³
- NAPHTHALENE**
OSHA PEL: 10 ppm, 50 mg/m³
OSHA TWA: 10 ppm, 50 mg/m³
ACGIH TWA: 10 ppm, 52 mg/m³
OSHA STEL: 15 ppm, 75 mg/m³
ACGIH STEL: 15 ppm, 79 mg/m³
- CUMENE**
OSHA PEL: 50 ppm
OSHA TWA: 50 ppm, 245 mg/m³
ACGIH TWA: 50 ppm, 246 mg/m³
- 1,3,5-TRIMETHYLBENZENE**
ACGIH TWA: 25 ppm
- ETHYLBENZENE**
OSHA TWA: 100 ppm
OSHA STEL: 125 ppm

TNT Ultra

SDS Number: 61854

Revision Date: 5/13/2016

Page 4 of 5

ACGIH STEL: 125 ppm

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Amber
Physical State: Liquid
Solubility: Nil in water
Bulk Density: 7.5 lbs/gal at 60 F

10 STABILITY AND REACTIVITY

Chemical Stability: Product is stable under normal conditions.
Conditions to Avoid: High temperatures above 50 C (122 F), sparks, and open flame.
Materials to Avoid: Avoid strong oxidizing agents.
May burn or react violently to flourine/oxygen mixtures.

11 TOXICOLOGICAL INFORMATION

Repeated skin contact with this product may cause dermatitis or an oil acne.
No component is listed as a mutagen or teratogen.

EYE EFFECTS:

Solvent Petroleum Naphtha, slightly irritating (rabbit).
Vinyl Acetate Monomer is a severe eye irritant (rabbit).

SKIN EFFECTS:

Solvent Petroleum Naphtha, no deaths reported at 4 ml/kg (Rat). Slightly irritating (rabbit, 4 hour(s)).
2-Ethylhexyl Nitrate is harmful in contact with skin.
Vinyl Acetate Monomer, Skin absorption LD50 is 2,335 mg/kg in rabbits.

ACUTE ORAL EFFECTS:

Solvent Petroleum Naphtha, LD50, 10 ml/kg in rats.
Oral LD 50 for Vinyl Acetate Monomer is 2,920 mg/kg in rats.
Ethylene Glycol Monobutyl Ether, Oral LD50, 1.4 g/kg (Guinea Pig).
Naphthalene, Oral LD50, 2600 mg/kg (rat).

ACUTE INHALATION EFFECTS:

Solvent Petroleum Naphtha, no deaths at 710 ppm (v) (Rat) 4 Hour (s).
Vinyl Acetate Monomer, four hour inhalation LC50 is 4,000 ppm in rats.
Inhalation 1 hour LC50 is >633 ppm in guinea pig for Ethylene Glycol Monobutyl Ether.

12 ECOLOGICAL INFORMATION

Avoid exposing to the environment. Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. Based on calculations. This product contains components which may be persistent in the environment.

13 DISPOSAL CONSIDERATIONS

Dispose of waste material in accordance with all local, state/provincial, and national requirements.
Do not flush to surface water or drains.

TNT Ultra

SDS Number: 61854

Revision Date: 5/13/2016

Page 5 of 5

14 TRANSPORT INFORMATION

NA1993, Combustible liquid, n.o.s., Combustible liquid, PGIII, (Contains Petroleum Naphtha, Ethylene Glycol Monobutyl Ether)

This material is not regulated for US DOT transportation in quantities less than 119 Gallons.

If shipping overseas, or via air, the proper shipping name is: Flammable liquid, n.o.s., (Contains Petroleum naphtha, 1,2,4-Trimethylbenzene), 3, UN1993, PGIII.

15 REGULATORY INFORMATION

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act (TSCA).

16 OTHER INFORMATION

The information contained in this Safety Data Sheet relates only to the specific material designated. Lubriformance, LLC assumes no legal responsibility for use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Lubriformance, LLC.