

LUBRIFORMANCE

The Lubrication Performance Company

ULTRA-DRI[™] Moisture Dispersant/Deicer

DESCRIPTION:

Ultra-Dri is specifically designed to help reduce moisture in fuel storage and vehicle tanks. Excess moisture can lead to problems with rust and corrosion, bacteria, and poor fuel performance. Ultra-Dri helps to eliminate these problems by safely removing controlled amounts of moisture.

USES:

Ultra-Dri can be used in gasoline or diesel. Ultra-Dri can also be used as a deicer and lowers the freeze point of water to help prevent filter plugging problems and vehicle shutdown. Using Ultra-Dri in your fuel system also give you the following benefits:

- Contains no alcohol.
- Lowers the freeze point of water.
- Prevents rust and corrosion
- Helps to eliminate conditions for bacteria and algae.

APPLICATION:

Ultra-Dri will effectively remove excess moisture from fuel storage tanks at a maximum absorption rate of one part water to one part Ultra-Dri.

Ultra-Dri should be used at the following treatment ratio:

- 1 Gal. Ultra-Dri to 7500 Gal. of Fuel for normal use.
- 1 Gal. Ultra-Dri to 3750 Gal. of Fuel high water content.

APPLICATION: Reverse Phase Separation in E-10 Gasoline

- 1). Pump off as much of the water as you can, you will not be able to get it all.
- 2). Add Ultra Dri at a ratio of 1 gal to 1000 gal of fuel, you can go 1 gal. Ultra Dri to 500 Gal. of fuel if it is a severe case or you have difficulty getting the water pumped out.
- 3). At this point agitation is the key to success. It is recommended that you pump the mixture into a Bobtail and drive it around to mix up. You can also circulate the fuel.
- 4).The product will normally go back in suspension.
- 5). If you have any questions, please call us at Lubriformance.

SPECIFICATIONS:

Appearance	Clear, Colorless to light Amber
Specific Gravity	0.902
Density	7.53
Flash Point	144°F
Freeze Point	-85°F

LUBRIFORMANCE

2021 Reserve Dr., P.O. Box 1487 Canton, TX 75103 PH: 903-567-7236