

LUBRIFORMANCE

The Lubrication Performance Company

TNT-3K EXTREME™ ***Premium Diesel Additive***

DESCRIPTION:

TNT-3K EXTREME™ is a multi-purpose diesel package giving significantly enhanced power, performance and protection to both on and off road diesel fuels.

Today's Diesel Fuels can be an array of ULSD and Biodiesel blends that can post a world of new problems.

These fuels, though better for the environment, tend to have less power, lower lubricity, stability issues, and moisture problems and are easily contaminated with algae and bacteria.

Today's new "High Tech" diesel engines that have the High-Pressure Common Rail, (HPCR), fuel injection systems have also experienced many problems with today's new fuels.

Internal Diesel Injector Deposits, (IDID's), which are different from the deposits that form on the injector tips, can accumulate on the needles and plungers of the injectors and in low clearance areas of the injectors, causing sluggish operation and poor performance.

TNT-3K EXTREME™ has been formulated to meet these problems and provide cost effective solutions to the diesel fuel consumer. **TNT-3K EXTREME™** contains a special HPCR Detergent Package to meet the demands of these new systems and eliminate deposits in the injectors.

USES:

TNT-3K EXTREME™ can be used in both on and off road equipment. **TNT-3K EXTREME™** will improve the cetane of diesel by as much as 2 to 3 numbers, (Higher cetane numbers can be achieved by increased concentration levels), giving equipment operators increased power and performance.

By using **TNT-3K EXTREME™** on a regular basis, operators will notice an increase in efficiency and fuel economy by as much as 5%.

BENEFITS:

TNT-3K EXTREME™ provides the following benefits:

- * Contains a cetane enhancer to improve fuel power and fuel economy
- * Improves lubricity
- * Contains HPCR Detergent Package to eliminate deposits
- * Improves oxidative stability
- * Dispersants reduce problems with moisture
- * Inhibits rust and corrosion
- * Stabilizes diesel fuel
- * Helps prevent algae and bacteria.

TNT-3K EXTREME provides excellent protection against traditional coking as measured in the DW-10 test and the XUD-9 test

APPLICATION:

TNT-3K EXTREME™ Treatment ratio is 1 gallon per 3000 gallons of diesel fuel.

** A treatment ratio of 1 gallon per 1500 gallons of diesel fuel will increase performance in lubricity, cetane number and HPCR detergent package**

SPECIFICATIONS:

Density	7.54 lbs./gal
Pour Point	<-30° F
Flash Point	118°
Appearance	Clear, light amber liquid; aromatic odor

- This diesel fuel additive complies with the federal low sulfur requirements for use in on and off-road diesel equipment.

LUBRIFORMANCE

2021 Reserve Dr., P.O. Box 1487 Canton, TX 75103 PH: 903-567-7236