



Hot Water EXTRACT

Concentrate

DESCRIPTION:

Super Concentrated Hot Water Extract is formulated for today's steam type carpet extraction machines. Optical brighteners added to enhance fiber appearance.

Note: Prior to use, read all directions and warnings first. Always test fibers/ upholstery for color loss in an inconspicuous area prior to use. Due to the nature of the stain removal process, Lubriformance/ Klene Solutions will not accept any liability for damages to fiber colors.

DIRECTIONS FOR USE:

- 1). Vacuum thoroughly before extracting.
- 2). After selecting the correct dilution ratio, add the hot water extract to the holding tank or truck mount holding tank. (Water in holding tank should not exceed 140°F).
- 3). Extract as normal using overlapping strokes (DO NOT OVER WET).

DILUTION RATIOS

Lightly/ normal soiled fiber: Dilute 1 oz. concentrate to 1 gallon water.

Heavy soiled fiber: Dilute 2-5 oz. concentrate to 1 gallon water.

SPECIFICATIONS:

Appearance and Odor: Aqua Liquid with pleasant citrus odor.

Specific Gravity: (Water=1) 1

Ph: 9.4-9.8

Boiling point (P): 212 F (C) 100

Vapor Pressure 9mm/Hg): Same as water

Vapor Density (Air=1) N/D

Solubility in water: Complete